



Description

Energy saving
High Efficiency Lighting
High Lumens Technology


Specifications

Model Name	GKD-03	
Power Consumption	200W	
Light Source	SMD3030	
Correlated Color Temperature	CW/W/W	
Luminous Flux *	26000	
Luminous Efficacy *	130lm/W	
LED Driving Current *	300mA	
Color Rendering Index	80 Ra	
Light Distribution	60° 90° 120°	
LED Chip Manufacturer	Epistar chip	
Input Voltage	90-265V	
Input Current	Max0.253A	
Power Factor	>0.95	
Frequency	50 / 60 Hz	
Surge Protection	Line-Line 3KV, Line-FG 3KV	
Driver Type	Non-Isolated Constant Current (IC)	
Fixture & Driver Manufacturer	SWIN / Made in China	
Size (D*H)	400*79mm	
base	E27/E26/B22	
Material	Die-casting AL	
IP Rating	IP44	
Operating Temperature	-22°F ~ 122°F	-30°C ~ 50°C
Life Time	30,000 Hours (@77°F / 25°C)	
Warranty	2Years (12 hours usage per day)	
Certification	CE/EMC	
Option	Dim/Undim	
Parking	BY carton	
Option		
Control System	/	

*Tolerance : ± 5%

Photometry

See photometric .ies files for details.



4000K / 360°(Symmetric)